Références bibliographiques

[AT81] Avis (D.) et Toussaint (G. T.). – An efficient algorithm for decomposing a polygon into star-shaped pieces. *Pattern Recognition*, vol. 13, 1981, pp. 295–298.

[BJMM93] Benouamer (M.), Jaillon (P.), Michelucci (D.) et Moreau (J.-M.). – A lazy solution to imprecision in computational geometry. *In : Proc. 5th Canad. Conf. Comput. Geom.*, pp. 73–78. – Waterloo, Canada, 1993.

[CG89] Chazelle (B.) et Guibas (L. J.). – Visibility and intersection problems in plane geometry. *Discrete Comput. Geom.*, vol. 4, 1989, pp. 551–581.

[CGL85] Chazelle (B.), Guibas (L. J.) et Lee (D. T.). – The power of geometric duality. *BIT*, vol. 25, 1985, pp. 76–90.

[Chv75] Chvátal (V.). – A combinatorial theorem in plane geometry. *J. Combin. Theory Ser.*, vol. B 18, 1975, pp. 39–41.

[CPT96] Chiang (Y.-J.), Preparata (F. P.) et Tamassia (R.). – A unified approach to dynamic point location, ray shooting, and shortest paths in planar maps. *SIAM J. Comput.*, vol. 25, 1996, pp. 207–233.

[DY93] Dobrindt (K.) et Yvinec (M.). – Remembering conflicts in history yields dynamic algorithms. *In : Proc. 4th Annu. Internat. Sympos. Algorithms Comput. (ISAAC 93)*. pp. 21–30. – Springer-Verlag.

[EG86] Edelsbrunner (H.) et Guibas (L. J.). – Topologically sweeping an arrangement. *In : Proc. 18th Annu. ACM Sympos. Theory Comput.*, pp. 389–403.

[EG89] Edelsbrunner (H.) et Guibas (L. J.). – Topologically sweeping an arrangement. *J. Comput. Syst. Sci.*, vol. 38, 1989, pp. 165–194. – Corrigendum in 42 (1991), 249–251.

[EM90] Edelsbrunner (H.) et Mücke (E. P.). – Simulation of simplicity: a technique to cope with degenerate cases in geometric algorithms. *ACM Trans. Graph.*, vol. 9, 1990, pp. 66–104.

[EOS86] Edelsbrunner (H.), O'Rourke (J.) et Seidel (R.). – Constructing arrangements of lines and hyperplanes with applications. *SIAM J. Comput.*, vol. 15, 1986, pp. 341–363.

[GHL+87] Guibas (L. J.), Hershberger (J.), Leven (D.), Sharir (M.) et Tarjan (R. E.). – Linear-time algorithms for visibility and shortest path problems inside triangulated simple polygons. *Algorithmica*, vol. 2, 1987, pp. 209–233.

[GM91] Ghosh (S. K.) et Mount (D. M.). – An output-sensitive algorithm for computing visibility graphs. *SIAM J. Comput.*, vol. 20, 1991, pp. 888–910.

[GSS89] Guibas (L. J.), Salesin (D.) et Stolfi (J.). – Epsilon geometry: building robust algorithms from imprecise computations. *In : Proc. 5th Annu. ACM Sympos. Comput. Geom.*, pp. 208–217.

[HM90] Heffernan (P. J.) et Mitchell (J. S. B.). – Structured visibility profiles with applications to problems in simple polygons. *In : Proc. 6th Annu. ACM Sympos. Comput. Geom.*, pp. 53–62.

[LPW79] Lozano-Pérez (T.) et Wesley (M. A.). – An algorithm for planning collision-free paths among polyhedral obstacles. *Commun. ACM*, vol. 22, 1979, pp. 560–570.

[O'R87] O'Rourke (J.). – *Art Gallery Theorems and Algorithms.* – New York, NY, Oxford University Press, 1987.

[ORDP96] Orti (R.), Rivière (S.), Durand (F.) et Puech (C.). – Radiosity for dynamic scenes in flatland with the visibility complex. *Comput. Graph. Forum*, vol. 15, n° 3, 1996, pp. 237–248. – Proc. Eurographics '96.

[OvL81] Overmars (M. H.) et van Leeuwen (J.). – Maintenance of configurations in the plane. *J. Comput. Syst. Sci.*, vol. 23, 1981, pp. 166–204.

[OW88] Overmars (M. H.) et Welzl (E.). – New methods for computing visibility graphs. *In : Proc. 4th Annu. ACM Sympos. Comput. Geom.*, pp. 164–171.

[Poc90] Pocchiola (M.). – Graphics in Flatland revisited. *In : Proc. 2nd Scand. Workshop Algorithm Theory*. pp. 85–96. – Springer-Verlag.

[PV93] Pocchiola (M.) et Vegter (G.). – Sweep algorithm for visibility graphs of curved obstacles. – manuscrit, 1993.

[PV94] Pocchiola (M.) et Vegter (G.). – *Order types and visibility types of configurations of disjoint convex plane sets.* – Rapport technique n° LIENS-94-4, Liens, Ecole Norm. Sup., Paris, janvier 1994.

[PV96a] Pocchiola (M.) et Vegter (G.). – Topologically sweeping visibility complexes via pseudo-triangulations. *Discrete Comput. Geom.*, décembre 1996. – To appear in the special issue devoted to ACM-SoCG'95.

[PV96b] Pocchiola (M.) et Vegter (G.). – The visibility complex. 1996. – To appear in the special issue devoted to ACM-SoCG'93.

[Sam84] Samet (H.). – The quadtree and related hierarchical data structures. *ACM Comput. Surv.*, vol. 16, n° 2, juin 1984.

[Sei94] Seidel (R.). – The nature and meaning of perturbations in geometric computing. *In : Proc. 11th Annu. Sympos. on Theorical Aspects of Computer Science (STACS 94)*. pp. 3–17. – Springer-Verlag.

[ST86] Sarnak (N.) et Tarjan (R. E.). – Planar point location using persistent search trees. *Commun. ACM*, vol. 29, 1986, pp. 669–679.

[Veg90] Vegter (G.). – The visibility diagram: A data structure for visibility problems and motion planning. *In : Proc. 2nd Scand. Workshop Algorithm Theory*. pp. 97–110. – Springer-Verlag.

[Yapre] Yap (C.). – *Fundamental Problems in Algorithmic Algebra.* – Princeton University Press, à paraître.

[Yap90] Yap (C. K.). – A geometric consistency theorem for a symbolic perturbation scheme. *J. Comput. Syst. Sci.*, vol. 40, 1990, pp. 2–18.

[YD95] Yap (C.) et Dubé (T.). – *Computing in Euclidean Geometry*. – World Scientific, 1995, 2 édition, *Lecture Notes Series on Computing*, volume 1.